



U74AHC32

CMOS IC


QUADRUPLE 2-INPUT POSITIVE-OR GATES

■ DESCRIPTION

The UTC **U74AHC32** are quadruple 2-input positive-or gates which provides the function $Y=A+B$ in positive logic.

■ FEATURES

- * Operate from 2V to 5.5V
- * Max t_{PD} of 7.5ns at 5 V
- * Low Power Dissipation: $I_{CC}=2\mu A(\text{Max})$ at $T_a=25^\circ C$
- * Halogen Free




■ ORDERING INFORMATION

Ordering Number	Package	Packing
U74AHC32G-P14-R	TSSOP-14	Tape Reel
U74AHC32G-S14-R	SOP-14	Tape Reel

<p>U74AHC32G-P14-R</p> <p>(1) Packing Type (2) Package Type (3) Halogen Free</p>	<p>(1) R: Tape Reel (2) P14: TSSOP-14, S14: SOP-14 (3) G: Halogen Free</p>
--	--

■ PIN CONFIGURATION




■ FUNCTION TABLE

INPUTS(A)	INPUTS(B)	OUTPUT(Y)
H	X	H
X	H	H
L	L	L

Note: H: HIGH voltage level; L: LOW voltage level.

■ LOGIC DIAGRAM



■ ABSOLUTE MAXIMUM RATING

PARAMETER	SYMBOL	RATINGS	UNIT
Supply Voltage	V_{CC}	-0.5 ~ +7	V
Input Voltage	V_{IN}	-0.5 ~ +7	V
Output Voltage	V_{OUT}	-0.5 ~ $V_{CC} + 0.5$	V
V_{CC} or GND Current	I_{CC}	±50	mA
Continuous Output Current	I_{OUT}	±25	mA
Input Clamp Current	I_{IK}	-20	mA
Output Clamp Current	I_{OK}	±20	mA
Operating Temperature	T_{OPR}	-40 ~ + 85	°C
Storage Temperature	T_{STG}	-65 ~ + 150	°C

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged. Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ THERMAL DATA

PARAMETER	SYMBOL	RATINGS	UNIT
Junction to Ambient	TSSOP-14	113	°C/W
	SOP-14	76	

■ RECOMMENDED OPERATING CONDITIONS

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Supply Voltage	V_{CC}		2		5.5	V
High-Level Input Voltage	V_{IH}	$V_{CC}=2V$	1.5			V
		$V_{CC}=3V$	2.1			V
		$V_{CC}=5.5V$	3.85			V
Low-Level Input Voltage	V_{IL}	$V_{CC}=2V$			0.5	V
		$V_{CC}=3V$			0.9	V
		$V_{CC}=5.5V$			1.65	V
Input Voltage	V_{IN}		0		5.5	V
Output Voltage	V_{OUT}	High or Low State	0		V_{CC}	V
High-Level Output Current	I_{OH}	$V_{CC}=2V$			-50	μA
		$V_{CC}=3.3V \pm 0.3V$			-4	mA
		$V_{CC}=5V \pm 0.5V$			-8	mA
Low-Level Output Current	I_{OL}	$V_{CC}=2V$			50	μA
		$V_{CC}=3.3V \pm 0.3V$			4	mA
		$V_{CC}=5V \pm 0.5V$			8	mA
Input Rise or Fall Times	$\frac{\Delta t}{\Delta V}$	$V_{CC}=3.3V \pm 0.3V$			100	ns/V
		$V_{CC}=5V \pm 0.5V$			20	ns/V

■ ELECTRICAL CHARACTERISTICS (Ta=25°C , unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS		MIN	TYP	MAX	UNIT
High-Level Output Voltage	V _{OH}	I _{OH} =-50μA	V _{CC} =2.0V	1.9	2.0		V
			V _{CC} =3.0V	2.9	3.0		V
			V _{CC} =4.5V	4.4	4.5		V
		I _{OH} =-4mA	V _{CC} =3.0V	2.58			V
		I _{OH} =-8mA	V _{CC} =4.5V	3.94			V
Low-Level Output Voltage	V _{OL}	I _{OL} =50μA	V _{CC} =2.0V			0.1	V
			V _{CC} =3.0V			0.1	V
			V _{CC} =4.5V			0.1	V
		I _{OL} =4mA	V _{CC} =3.0V			0.36	V
		I _{OL} =8mA	V _{CC} =4.5V			0.36	V
Input Leakage Current	I _{I(LEAK)}	V _{IN} =5.5V or GND	V _{CC} =0 to 5.5V			±0.1	μA
Quiescent Supply Current	I _Q	V _{IN} =V _{CC} or GND I _{OUT} =0	V _{CC} =5.5V			2	μA
Input Capacitance	C _{IN}	V _{IN} =V _{CC} or GND	V _{CC} =5.0V		2	10	pF


■ SWITCHING CHARACTERISTICS (see TEST CIRCUIT AND WAVEFORMS)

PARAMETER	SYMBOL	TEST CONDITIONS		MIN	TYP	MAX	UNIT
Propagation delay from input (A or B) to output(Y)	t _{PLH} / t _{PHL}	V _{CC} =3.3V±0.3V	C _L =15 pF		5.5	7.9	ns
			C _L =50 pF		8	11.4	ns
		V _{CC} =5.0V±0.5V	C _L =15 pF		3.8	5.5	ns
			C _L =50 pF		5.3	7.5	ns


■ OPERATING CHARACTERISTICS (Ta=25°C)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Power Dissipation Capacitance	C _{PD}	No load, f=1MHz, V _{CC} =5V		14		pF


■ TEST CIRCUIT AND WAVEFORMS



TEST	S
t _{PLH} /t _{PHL}	Open
t _{PHZ} /t _{PZH}	GND
t _{PLZ} /t _{PZL}	V _{CC}



SETUP TIME AND HOLD TIME



PROPAGATION DELAY TIMES

Note: C_L includes probe and jig capacitance.
 PRR ≤ 1MHz, Z_O = 50Ω, t_R ≤ 3ns, t_F ≤ 3ns.

UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.