



UT136FE**TRIAC****TRIAC****■ DESCRIPTION**

Glass passivated sensitive gate triacs in a full pack, plastic envelop, intended for use in general purpose bidirectional switching and phase control applications, where high sensitivity is required in all four quadrants




TO-220F

■ SYMBOL**■ ORDERING INFORMATION**

Ordering Number		Package	Pin Description			Packing
Lead Free	Halogen Free		1	2	3	
UT136FEL-x-TF3-R	UT136FEG-x-TF3-R	TO-220F	MT1	MT2	G	Tube

Note: Pin Assignment: G: Gate

UT136FEG-x-TF3-R 	(1) T: Tube (2) TF3: TO-220F (3) 5: 500V, 6: 600V, 8: 800V (4) G: Halogen Free and Lead Free, L: Lead Free
----------------------	---

■ MARKING

■ ABSOLUTE MAXIMUM RATING

PARAMETER		SYMBOL	RATINGS	UNIT
Repetitive Peak Off-State Voltages	UT136FE-5	V_{DRM}	500 (Note2)	V
	UT136FE-6		600 (Note2)	
	UT136FE-8		800	
RMS On-state Current Full sine wave, $T_{HS} \leq 92^\circ C$		$I_{T(RMS)}$	4	A
Non-Repetitive Peak. On-State Current Full sine wave, $T_J = 125^\circ C$ prior to surge, with reapplied $V_{DRM(MAX)}$	$t = 20\text{ ms}$	I_{TSM}	25	A
	$t = 16.7\text{ ms}$		27	
I^2t For Fusing ($t = 10\text{ ms}$)		I^2t	3.1	$A^2\text{s}$
Repetitive Rate of Rise of On-state Current after Triggering $I_{TM}=12\text{ A}$, $I_G=0.2\text{ A}$, $dI_G/dt=0.2\text{ A}/\mu\text{s}$	T2 + G+	dI_T/dt	50	$\text{A}/\mu\text{s}$
	T2 + G-		50	
	T2 - G-		50	
	T2 - G+		10	
Peak Gate Voltage		V_{GM}	5	V
Peak Gate Current		I_{GM}	2	A
Peak Gate Power		P_{GM}	5	W
Average Gate Power (Over any 20ms period)		$P_{G(AV)}$	0.5	W
Operating Junction Temperature		T_J	+125	$^\circ C$
Storage Temperature		T_{STG}	-40 ~ +150	$^\circ C$

Notes: 1. Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

2. Although not recommended, off-state voltages up to 800V may be applied without damage, but the triac may switch to the on-state. The rate of rise of current should not exceed 3A/ μs .

■ THERMAL RESISTANCES

PARAMETER		SYMBOL	MIN	TYP	MAX	UNIT
Thermal resistance Junction to Ambient	In Free Air	θ_{JA}		55		$^\circ C/W$
Thermal resistance Junction to mounting base	Full cycle	θ_{JC}			5.5	$^\circ C/W$
	Half cycle				7.2	$^\circ C/W$

■ ISOLATION LIMITING VALUE & CHARACTERISTIC ($T_{HS}=25^\circ C$, unless otherwise specified)

PARAMETER		SYMBOL	MIN	TYP	MAX	UNIT
Repetitive peak voltage form all three terminals to external heatsink (R.H. $\leq 65\%$, clean and dustfree)		V_{ISOL}			1500	V
Capacitance from MT2 to external heatsink ($f = 1\text{ MHz}$)		C_{ISOL}		12		pF

■ **STATIC CHARACTERISTICS** ($T_J = 25^\circ\text{C}$, unless otherwise specified)


PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Gate Trigger Current	I_{GT}	$V_D = 12 \text{ V}, I_T = 0.1 \text{ A}$	T2 + G+		10	mA
			T2 + G-		10	mA
			T2 - G-		10	mA
			T2 - G+		25	mA
Latching Current	I_L	$V_D = 12 \text{ V}, I_{GT} = 0.1 \text{ A}$	T2 + G+		15	mA
			T2 + G-		20	mA
			T2 - G-		15	mA
			T2 - G+		20	mA
Holding Current	I_H	$V_D = 12 \text{ V}, I_{GT} = 0.1 \text{ A}$			15	mA
On-State Voltage	V_T	$I_T = 5 \text{ A}$			1.7	V
Gate Trigger Voltage	V_{GT}	$V_D = 12 \text{ V}, I_T = 0.1 \text{ A}$			1.5	V
		$V_D = 400 \text{ V}, I_T = 0.1 \text{ A}, T_J = 125^\circ\text{C}$	0.25			V
Off-State Leakage Current	I_D	$V_D = V_{DRM(MAX)}, T_J = 125^\circ\text{C}$			0.5	mA

■ **DYNAMIC CHARACTERISTICS** ($T_J = 25^\circ\text{C}$, unless otherwise specified)


PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Critical Rate of Rise of Off-State Voltage	dV_D/dt	$V_{DM} = 67\% V_{DRM(MAX)}, T_J = 125^\circ\text{C}$, Exponential waveform, gate open circuit		50		V/ μs
Gate Controlled Turn-On Time	t_{GT}	$I_{TM} = 6 \text{ A}, V_D = V_{DRM(MAX)}, I_G = 0.1 \text{ A}, dI_G/dt = 5 \text{ A}/\mu\text{s}$		2		μs

■ TYPICAL CHARACTERISTICS


Maximum On -State Dissipation. P_{Tot} vs. RMS On-State Current, $I_{\text{T(RMS)}}$, Where α =conduction Angle




Maximum Permissible RMS Current $I_{\text{T(RMS)}}$ vs. Versus Heatsink Temperature T_{hs}




Maximum Permissible Non-Repetitive Peak On-State Current I_{TSM} vs. Pulse Width t_p , for Sinusoidal Currents, $t_p \leq 20\text{ms}$




Maximum Permissible Repetitive RMS On-State Current $I_{\text{T(RMS)}}$ vs. Versus Surge Duration, for Sinusoidal Currents, $f=50\text{Hz}$, $T_{\text{hs}} \leq 92^\circ\text{C}$









Maximum Permissible Non-Repetitive Peak On-State Current I_{TSM} vs. Number of Cycles, for Sinusoidal Currents, $f=50\text{Hz}$



Normalised Gate Trigger Voltage $V_{\text{GT}}(T_J)/V_{\text{GT}}(25^\circ\text{C})$ vs. Junction Temperature T_J



■ TYPICAL CHARACTERISTICS (Cont.)



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

