



## BC856/BC857/BC858


## PNP SILICON TRANSISTOR

### SWITCHING AND AMPLIFIER APPLICATIONS


#### FEATURES

\*Suitable for automatic insertion in thick and thin-film circuits

\*Complement to BC846/BC847/BC848



SOT-23  
(JEDEC TO-236)



SOT-323

#### ORDERING INFORMATION

Ordering Number		Package	Pin Assignment			Packing
Lead Free	Halogen Free		1	2	3	
BC856L-x-AE3-R	BC856G-x-AE3-R	SOT-23	B	E	C	Tape Reel
BC857L-x-AE3-R	BC857G-x-AE3-R	SOT-23	B	E	C	Tape Reel
BC858L-x-AE3-R	BC858G-x-AE3-R	SOT-23	B	E	C	Tape Reel
BC856L-x-AL3-R	BC856G-x-AL3-R	SOT-323	B	E	C	Tape Reel
BC857L-x-AL3-R	BC857G-x-AL3-R	SOT-323	B	E	C	Tape Reel
BC858L-x-AL3-R	BC858G-x-AL3-R	SOT-323	B	E	C	Tape Reel

Note: Pin Assignment: B: Base E: Emitter C: Collector

<p>BC856G-x-AE3-R</p>	<p>(1) Packing Type</p> <p>(2) Package Type</p> <p>(3) Rank</p> <p>(4) Green Package</p>	<p>(1) R: Tape Reel</p> <p>(2) AE3: SOT-23, AL3: SOT-323</p> <p>(3) x: refer to Classification of h<sub>FE</sub></p> <p>(4) G: Halogen Free and Lead Free, L: Lead Free</p>
-----------------------	--	---

#### MARKING

BC856	BC857	BC858

Notes: 1. X: Rank Code, refer to Classification of h<sub>FE</sub>.

2. □: L: Lead Free, G: Halogen Free.

# BC856/BC857/BC858

## PNP SILICON TRANSISTOR

### ■ ABSOLUTE MAXIMUM RATINGS (T<sub>A</sub>=25°C, unless otherwise specified)

PARAMETER	SYMBOL	RATINGS	UNIT
Collector-Base Voltage	BC856	-80	V
	BC857	-50	V
	BC858	-30	V
Collector-Emitter Voltage	BC856	-65	V
	BC857	-45	V
	BC858	-30	V
Emitter-Base Voltage	V <sub>EBO</sub>	-5	V
Collector Dissipation	P <sub>D</sub>	310	mW
Collector Current (DC)	I <sub>C</sub>	-100	mA
Junction Temperature	T <sub>J</sub>	+150	°C
Operating Temperature Range	T <sub>OPR</sub>	-40 ~ +150	°C
Storage Temperature	T <sub>STG</sub>	-40 ~ +150	°C

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged. Absolute maximum ratings are stress ratings only and functional device operation is not implied.







### ■ ELECTRICAL CHARACTERISTICS (T<sub>A</sub>=25°C, unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Collector Cut-Off Current	I <sub>CBO</sub>	V <sub>CB</sub> =-30V, I <sub>E</sub> =0			-15	nA
DC Current Gain	h <sub>FE</sub>	V <sub>CE</sub> =-5V, I <sub>C</sub> =-2mA	110		800	
Collector-Emitter Saturation Voltage	V <sub>CE(SAT)</sub>	I <sub>C</sub> =-10mA, I <sub>B</sub> =-0.5mA		-90	-300	mV
		I <sub>C</sub> =-100mA, I <sub>B</sub> =-5mA		-250	-650	mV
Base-Emitter Saturation Voltage	V <sub>BE(SAT)</sub>	I <sub>C</sub> =-10mA, I <sub>B</sub> =-0.5mA		-700		mV
		I <sub>C</sub> =-100mA, I <sub>B</sub> =-5mA		-900		mV
Base-Emitter On Voltage	V <sub>BE(ON)</sub>	V <sub>CE</sub> =-5V, I <sub>C</sub> =-2mA	-600	-660	-750	mV
		V <sub>CE</sub> =-5V, I <sub>C</sub> =-10mA			-800	mV
Current Gain Bandwidth Product	f <sub>T</sub>	V <sub>CE</sub> =-5V, I <sub>C</sub> =-10mA, f=100MHz		150		MHz
Output Capacitance	C <sub>ob</sub>	V <sub>CB</sub> =-10V, I <sub>E</sub> =0, f=1MHz			6	pF
Noise Figure	NF	V <sub>CE</sub> =-5V, I <sub>C</sub> =-200μA, f=1KHz, R <sub>G</sub> =2KΩ		2	10	dB

### ■ CLASSIFICATION OF h<sub>FE</sub>

RANK	A	B	C
RANGE	110-220	200-450	420-800

## TYPICAL CHARACTERISTICS



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.