

LR1122D

CMOS IC

LOW NOISE 200mA LDO REGULATOR

■ DESCRIPTION

The UTC **LR1122D** is a typical LDO (linear regulator) with the features of high output voltage accuracy, low supply current, low ON-resistance, and high ripple rejection.

During operation of the UTC **LR1122D**, the dropout voltage is very low and the response of line transient and load transient are very well.

Internally, there're many functions of UTC **LR1122D** which can be seen in the block figure. There are a voltage reference unit, an error amplifier, resistor-net for voltage setting, a current limit circuit, and a chip enable circuit in each UTC **LR1122D**.

The UTC **LR1122D** can be used as an ideal of the power supply for hand-held communication equipment, such as: power source for portable communication equipment, power source for electrical appliances, for example, cameras, VCRs and camcorders and power source for battery-powered equipment.


■ FEATURES

* Ultra Supply Current:	20µA (Typ.)
* Standby Mode:	0.1µA (Typ.)
* Very Low Dropout Voltage:	0.13V (Typ.) @ $I_{OUT}=150mA, V_{OUT}=2.85V$
* Ripple Rejection:	75dB (Typ.) @ $f=1kHz, V_{OUT}=2.85V$
* Temperature-Drift Coefficient of Output Voltage:	±30ppm/°C (Typ.)
* Well Line Regulation:	0.02%/ V (Typ.)
* Output Voltage Accuracy:	±1.0% (Typ.)
* Internal Fold Back Protection Circuit:	40mA (Typ.) @ short mode
* $C_{IN}=C_{OUT}=1\mu F$ or more (Ceramic capacitors) are recommended to be used with this IC	

■ ORDERING INFORMATION

Ordering Number		Package	Pin Assignment					Packing
Lead Free	Halogen Free		1	2	3	4	5	
LR1122DL-xx-AB3-C-R	LR1122DG-xx-AB3-C-R	SOT-89	G	I	O	-	-	Tape Reel
LR1122DL-xx-AF5-R	LR1122DG-xx-AF5-R	SOT-25	I	G	CE	NC	O	Tape Reel


Note: xx: Output Voltage, refer to Marking Information.

 <ul style="list-style-type: none"> (1)Packing Type (2)Pin Assignment (3)Package Type (4)Output Voltage Code (5)Green Package 	<ul style="list-style-type: none"> (1) R: Tape Reel (2) refer to Pin Assignment (3) AB3: SOT-89, AF5: SOT-25 (4) xx: Refer to Marking Information (5) G: Halogen Free and Lead Free, L: Lead Free
---	--

■ MARKING INFORMATION

PACKAGE	VOLTAGE CODE	MARKING
SOT-89	12: 1.2V	
	15: 1.5V	
	16: 1.6V	
	18: 1.8V	
	20: 2.0V	
	22: 2.2V	
SOT-25	25: 2.5V	
	2J: 2.85V	
	30: 3.0V	
	33: 3.3V	
	50: 5.0V	


■ PIN CONFIGURATION



■ PIN DESCRIPTIONS

PIN NAME	DESCRIPTION
V_{IN}	Input Pin
GND	Ground Pin
CE	Chip Enable Pin. Active when this Pin is high.
NC	No Connection
V_{OUT}	Output Pin

■ BLOCK DIAGRAM



■ ABSOLUTE MAXIMUM RATING

PARAMETER		SYMBOL	RATINGS		UNIT
Input Voltage		V _{IN}	9		V
Input Voltage(CE Pin)		V _{CE}	8.5		V
Output Voltage		V _{OUT}	-0.3~V _{IN} +0.3		V
Output Current		I _{OUT}	200		mA
Power Dissipation	SOT-25	P _D	360		mW
	SOT-89		530		
Junction Temperature		T _J	+125		°C
Operating Temperature		T _{OPR}	-40 ~ +85		°C
Storage Temperature		T _{STG}	-55 ~ +125		°C

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged.


Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ ELECTRICAL CHARACTERISTICS


(T_A=25°C, V_{IN}=Set V_{OUT}+1V, I_{OUT}=1mA, C_I=C_O=1μF, unless otherwise specified)

PARAMETER		SYMBOL	TEST CONDITIONS		MIN	TYP	MAX	UNIT	
Output Voltage		V _{OUT}	V _{IN} = Set V _{OUT} +1V		V _{OUT} > 2.0V	×0.99		×1.01	V
			I _{OUT} =30mA		V _{OUT} ≤ 2.0V	-20		+20	mV
Input Voltage		V _{IN}					7.5	V	
Load Regulation		ΔV _{OUT}	1mA ≤ I _{OUT} ≤ 150mA			20	40	mV	
Output Current		I _{OUT}			200			mA	
Supply Current		I _{SS}	I _{OUT} =0A			20	40	μA	
Supply Current (Standby)		I _{ST-BY}	V _{CE} =0V			0.1	2	μA	
Short Current Limit		I _{LIMIT}	V _{OUT} =0V			40		mA	
CE Pull-down Current		I _{PD}				0.3		μA	
CE Input Voltage	High	V _{CEH}			1.5			V	
	Low	V _{CEL}					0.3	V	
Output Noise		eN	B _W =10Hz to 100kHz, I _{OUT} =30mA			30		μVrms	
Ripple Rejection		RR	f=1kHz, Ripple 0.2V _{P-P} V _{IN} =Set V _{OUT} +1V, I _{OUT} =30mA (In case that V _{OUT} =2.0V, V _{IN} =3V)			75		dB	
Dropout Voltage		V _D	I _{OUT} =150mA		1.2V ≤ V _{OUT} < 1.5V	0.90	1.00	V	
					1.5V ≤ V _{OUT} < 1.7V	0.60	0.80		
					1.7V ≤ V _{OUT} < 2.0V	0.21	0.36		
					2.0V ≤ V _{OUT} < 2.5V	0.17	0.30		
					2.5V ≤ V _{OUT} < 2.8V	0.14	0.25		
					2.8V ≤ V _{OUT} ≤ 5.0V	0.13	0.23		
Line Regulation		$\frac{\Delta V_{OUT}}{\Delta V_{IN}}$	1.2V ≤ V _{OUT} ≤ 4.0V, V _{SET} +1V ≤ V _{IN} ≤ 5V			0.02	0.30	%/V	
			4.0V < V _{OUT} ≤ 5.0V, V _{SET} +1V ≤ V _{IN} ≤ 6.5V						
Output Voltage Temperature Coefficient		$\frac{\Delta V_{OUT}}{\Delta T}$	-40°C ≤ T _{OPR} ≤ 85°C			±30		ppm/°C	
Low Output Nch Tr. ON Resistance		R _{LOW}	V _{IN} =4.0, V _{CE} =0V			70		Ω	


■ TEST CIRCUIT




Basic Test Circuit



Test Circuit for Supply Current




Test Circuit for Ripple Rejection









Test Circuit for Load Transient Response







■ TYPICAL APPLICATION CIRCUIT



■ TYPICAL CHARACTERISTICS



■ TYPICAL CHARACTERISTICS (Cont.)



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

