



U74AHC14

CMOS IC


HEX SCHMITT-TRIGGER INVERTERS

DESCRIPTION


The **U74AHC14** is hex Schmitt-trigger inverters and each inverter provides the function $Y = \overline{A}$.

FEATURES

- * Operation Voltage Range: 2V ~ 5.5V
- * Max t_{PD} of 8.6ns at 5V ($C_L=15pF$)
- * High Noise Immunity
- * Low Power Dissipation



SOP-14U




TSSOP-14U

ORDERING INFORMATION


Ordering Number		Package	Packing
Lead Free	Halogen Free		
U74AHC14L-UEA-R	U74AHC14G-UEA-R	SOP-14U	Tape Reel
U74AHC14L-UEB-R	U74AHC14G-UEB-R	TSSOP-14U	Tape Reel

U74AHC14G-UEA-R




- (1) R: Tape Reel
- (2) UEA: SOP-14U, UEB: TSSOP-14U
- (3) G: Halogen Free and Lead Free, L: Lead Free

MARKING



■ PIN CONFIGURATION




■ FUNCTION TABLE (each gate)

INPUT A	OUTPUT Y
L	H
H	L

Note: H: HIGH voltage level; L: LOW voltage level.

■ LOGIC SYMBOL



■ ABSOLUTE MAXIMUM RATING (T_A=25°C, unless otherwise specified)

PARAMETER	SYMBOL	RATINGS	UNIT
Supply Voltage	V _{CC}	-0.5 ~ +7	V
Input Voltage	V _{IN}	-0.5 ~ +7	V
Output Voltage	V _{OUT}	-0.5 ~ V _{CC} +0.5	V
Input Clamp Current	I _{IK}	-20	mA
Output Clamp Current	I _{OK}	±20	mA
Output Sink Current	I _{OUT}	±25	mA
V _{CC} or GND Current	I _{CC}	±50	mA
Storage Temperature	T _{STG}	-65 ~ + 150	°C

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged.
Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ RECOMMENDED OPERATING CONDITIONS (T_A=25°C, unless otherwise specified)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNIT
Supply Voltage	V _{CC}		2.0		5.5	V
Input Voltage	V _{IN}		0		5.5	V
Output Voltage	V _{OUT}		0		V _{CC}	V
High-Level Input Current	I _{OH}	V _{CC} =2V			-50	μA
		V _{CC} =3.3V±0.3V			-4	mA
		V _{CC} =5V±0.5V			-8	mA
Low-Level Input Current	I _{OL}	V _{CC} =2V			50	μA
		V _{CC} =3.3V±0.3V			4	mA
		V _{CC} =5V±0.5V			8	mA
Operating Temperature	T _A		-40		+125	°C

■ THERMAL DATA

PARAMETER	SYMBOL	RATINGS	UNIT
Junction to Ambient	SOP-14U	125	°C/W
	TSSOP-14U	150	°C/W

■ STATIC CHARACTERISTICS (Unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	T _A =25°C			T _A =-40~+125°C			UNIT
			MIN	TYP	MAX	MIN	TYP	MAX	
Positive-going Input Threshold Voltage	V _{T+}	V _{CC} =3.0V	1.2		2.2	1.2		2.2	V
		V _{CC} =4.5V	1.75		3.15	1.75		3.15	V
		V _{CC} =5.5V	2.15		3.85	2.15		3.85	V
Negative-going Input Threshold Voltage	V _{T-}	V _{CC} =3.0V	0.9		1.9	0.9		1.9	V
		V _{CC} =4.5V	1.35		2.75	1.35		2.75	V
		V _{CC} =5.5V	1.65		3.35	1.65		3.35	V
Hysteresis(V _{T+} - V _{T-})	ΔV _T	V _{CC} =3.0V	0.3		1.2	0.25		1.2	V
		V _{CC} =4.5V	0.4		1.4	0.35		1.4	V
		V _{CC} =5.5V	0.5		1.6	0.45		1.6	V
High-Level Output Voltage	V _{OH}	I _{OH} = -50μA	V _{CC} =2.0V	1.9		1.9			V
			V _{CC} =3.0V	2.9		2.9			V
			V _{CC} =4.5V	4.4		4.4			V
		I _{OH} = -4mA	V _{CC} =3.0V	2.58		2.40			V
		I _{OH} = -8mA	V _{CC} =4.5V	3.94		3.70			V
Low-Level Output Voltage	V _{OL}	I _{OL} =50μA	V _{CC} =2.0V		0.1			0.1	V
			V _{CC} =3.0V		0.1			0.1	V
			V _{CC} =4.5V		0.1			0.1	V
		I _{OL} =4mA	V _{CC} =3.0V		0.36			0.55	V
		I _{OL} =8mA	V _{CC} =4.5V		0.36			0.55	V
Input Leakage Current	I _{I(LEAK)}	V _{CC} =0V to 5.5V, V _{IN} =5.5V or GND			±0.1			2	μA
Quiescent Supply Current	I _Q	V _{CC} =5.5V, V _{IN} =V _{CC} or GND, I _{OUT} =0			2			40	μA


■ SWITCHING CHARACTERISTICS (Unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	T _A =25°C			T _A =-40~+125°C			UNIT
			MIN	TYP	MAX	MIN	TYP	MAX	
Propagation Delay, From Input (A) To Output (Y)	t _{PLH} / t _{PHL}	V _{CC} =3.3±0.3V		8.3	12.8			16	ns
				10.8	16.3			20.5	ns
	t _{PLH} / t _{PHL}	V _{CC} =5.0±0.5V		5.5	8.6			11	ns
				7	10.6			13.5	ns


■ OPERATING CHARACTERISTICS (T_A=25°C, unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Input Capacitance	C _I	V _{IN} =V _{CC} or GND		2	10	pF
Power Dissipation Capacitance	C _{PD}	No Load, f=1MHz		9		pF

■ TEST CIRCUIT AND WAVEFORMS



Test circuit for measuring propagation delay



Waveforms showing the Input (A) to Output (Y) propagation delays

Notes: 1. C_L includes probe and jig capacitance.

2. All input pulses are supplied by generators having the following characteristics: $PRR \leq 1\text{MHz}$, $Z_o = 50\Omega$, $t_r \leq 3\text{ns}$, $t_f \leq 3\text{ns}$.

UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.