

**UCD40106B****CMOS IC****HEX SCHMITT TRIGGERS****DESCRIPTION**

The **UCD40106B** is a high speed Si-gate CMOS device which contains six independent Schmitt-trigger inverters and they perform the function $Y=\bar{A}$.

The device have different input threshold levels for positive-going (V_{T+}) and negative-going (V_{T-}) signals because of the Schmitt-trigger action in the input.

FEATURES

- * High voltage type (20V rating)
- * All inputs have Schmitt-trigger action
- * Hysteresis Voltage(TYP): 0.9V at $V_{CC}=5V$
2.3V at $V_{CC}=10V$
3.5V at $V_{CC}=15V$
- * Wide supply voltage range from 3V to 18V
- * Inputs are TTL-Voltage compatible
- * Noise immunity greater than 50%

ORDERING INFORMATION

Ordering Number		Package	Packing
Lead Free	Halogen Free		
UCD40106BL-D14-T	UCD40106BG-D14-T	DIP-14	Tube
UCD40106BL-UEA-R	UCD40106BG-UEA-R	SOP-14U	Tape Reel
UCD40106BL-UEB-R	UCD40106BG-UEB-R	TSSOP-14U	Tape Reel

UCD40106BG-D14-T

- (1) Packing Type
- (2) Package Type
- (3) Green Package

(1) T: Tube, R: Tape Reel


(2) D14: DIP-14, UEA: SOP-14U, UEB: TSSOP-14U

(3) G: Halogen Free and Lead Free, L: Lead Free

MARKING

DIP-14	SOP-14U / TSSOP-14U
14 13 12 11 10 9 8 UTC □□□□ UCD40106B □ □□ 1 2 3 4 5 6 7 → Date Code L: Lead Free G: Halogen Free → Lot Code	14 13 12 11 10 9 8 UTC □□□□ UCD40106B □ □□ 1 2 3 4 5 6 7 → Date Code L: Lead Free G: Halogen Free → Lot Code

PIN CONFIGURATION




FUNCTION TABLE (each gate)

INPUT	OUTPUT
A	Y
L	H
H	L

Note: H: HIGH voltage level; L: LOW voltage level

LOGIC DIAGRAM (positive logic)



■ **ABSOLUTE MAXIMUM RATING** ($T_A = 25^\circ\text{C}$, unless otherwise specified)(Note 1)

PARAMETER	SYMBOL	RATINGS	UNIT
Supply Voltage	V_{CC}	-0.5 ~ 20	V
Input Voltage	V_{IN}	-0.5 ~ $V_{CC}+0.5$	V
DC Input Current, Any One Input	I_{IN}	± 10	mA
Storage Temperature	T_{STG}	-65 ~ +150	$^\circ\text{C}$

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged.
Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ **RECOMMENDED OPERATING CONDITIONS**

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNIT
Supply Voltage	V_{CC}	Operating	3		18	V
Input Voltage	V_{IN}		0		V_{CC}	V
Operating Temperature	T_{OPR}		-40		+125	$^\circ\text{C}$

■ **THERMAL DATA**

PARAMETER		SYMBOL	RATINGS	UNIT
Junction to Ambient	DIP-14	θ_{JA}	75	$^\circ\text{C/W}$
	SOP-14U		105	$^\circ\text{C/W}$
	TSSOP-14U		135	$^\circ\text{C/W}$

■ **STATIC CHARACTERISTICS** ($T_A = 25^\circ\text{C}$, unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Positive-Going Input Threshold Voltage	V_{T+}	$V_{CC}=5\text{V}$	2.2	2.9	3.6	V
		$V_{CC}=10\text{V}$	4.6	5.9	7.1	
		$V_{CC}=15\text{V}$	6.6	8.8	10.8	
Negative-Going Input Threshold Voltage	V_{T-}	$V_{CC}=5\text{V}$	0.9	1.9	2.8	V
		$V_{CC}=10\text{V}$	2.5	3.9	5.2	
		$V_{CC}=15\text{V}$	4.0	5.8	7.4	
Hysteresis Voltage ($V_{T+}-V_{T-}$) (see figure 3)	ΔV_T	$V_{CC}=5\text{V}$	0.3	0.9	1.6	V
		$V_{CC}=10\text{V}$	1.2	2.3	3.6	
		$V_{CC}=15\text{V}$	1.6	3.5	5.0	
High-Level Output Voltage	V_{OH}	$V_{CC}=5\text{V}, I_O < 1\mu\text{A}$	4.95	5		V
		$V_{CC}=10\text{V}, I_O < 1\mu\text{A}$	9.95	10		
		$V_{CC}=15\text{V}, I_O < 1\mu\text{A}$	14.95	15		
Low-Level Output Voltage	V_{OL}	$V_{CC}=5\text{V}, I_O < 1\mu\text{A}$		0	0.05	V
		$V_{CC}=10\text{V}, I_O < 1\mu\text{A}$		0	0.05	
		$V_{CC}=15\text{V}, I_O < 1\mu\text{A}$		0	0.05	
High-level Output Current	I_{OH}	$V_{CC}=5\text{V}, V_O=4.6\text{V}$	-0.51	-1		mA
		$V_{CC}=5\text{V}, V_O=2.5\text{V}$	-1.6	-3.2		
		$V_{CC}=10\text{V}, V_O=9.5\text{V}$	-1.3	-2.6		
		$V_{CC}=15\text{V}, V_O=13.5\text{V}$	-3.4	-6.8		
Low-level Output Current	I_{OL}	$V_{CC}=5\text{V}, V_O=0.4\text{V}$	0.51	1.0		mA
		$V_{CC}=10\text{V}, V_O=0.5\text{V}$	1.3	2.6		
		$V_{CC}=15\text{V}, V_O=1.5\text{V}$	3.4	6.8		
Input Leakage Current	$I_{I(LEAK)}$	$V_{CC}=18\text{V}, V_{IN}=V_{CC}$ or GND		± 0.01	± 100	nA
Quiescent Supply Current	I_{DD}	$V_{CC}=5\text{V}, V_{IN}=V_{CC}$ or GND, $I_{OUT}=0$		0.02	1	uA
		$V_{CC}=10\text{V}, V_{IN}=V_{CC}$ or GND, $I_{OUT}=0$		0.02	2	
		$V_{CC}=15\text{V}, V_{IN}=V_{CC}$ or GND, $I_{OUT}=0$		0.02	4	
		$V_{CC}=20\text{V}, V_{IN}=V_{CC}$ or GND, $I_{OUT}=0$		0.04	20	

■ **DYNAMIC CHARACTERISTICS** ($T_A = 25^\circ\text{C}$, unless otherwise specified; Input: $t_r, t_f=20\text{ns}$)


See Fig. 1 and Fig. 2 for test circuit and waveforms.

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Propagation delay from input (A) to output(Y)	t_{PLH}/t_{PHL}	$V_{CC}=5\text{V}, C_L=50\text{pF}, R_L=200\text{K}\Omega$		140	280	ns
		$V_{CC}=10\text{V}, C_L=50\text{pF}, R_L=200\text{K}\Omega$		70	140	
		$V_{CC}=15\text{V}, C_L=50\text{pF}, R_L=200\text{K}\Omega$		60	120	
Output Transition Time	t_{TLH}/t_{THL}	$V_{CC}=5\text{V}, C_L=50\text{pF}, R_L=200\text{K}\Omega$		100	200	ns
		$V_{CC}=10\text{V}, C_L=50\text{pF}, R_L=200\text{K}\Omega$		50	100	
		$V_{CC}=15\text{V}, C_L=50\text{pF}, R_L=200\text{K}\Omega$		40	80	

■ **OPERATING CHARACTERISTICS**

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Average Input Capacitance	C_{IN}	Any Input		5	7.5	pF
Power Dissipation Capacitance	C_{PD}	Any Gate		14		pF

■ TEST CIRCUIT AND WAVEFORMS



Note: C_L includes probe and jig capacitance.

Fig. 1 Load circuitry for switching times.




Fig. 2 Propagation delay from input(A) to output(Y) and Output transition time.

■ TEST CIRCUIT AND WAVEFORMS(Cont.)




Fig. 3 Hysteresis definition, characteristics, and test setup

UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.