



MBR10150

Preliminary

DIODE

10A SCHOTTKY BARRIER RECTIFIER

DESCRIPTION


The UTC **MBR10150** is a 10A schottky barrier rectifier, it uses UTC's advanced technology to provide the customers with high surge capability, high efficiency, high current capability, low power loss and low forward voltage drop, etc.

The UTC **MBR10150** is suitable for free wheeling and polarity protection, etc.

FEATURES

- * Low Reverse Current
- * Low Stored Charge, Majority Carrier Conduction
- * Low Power Loss/High Efficiency
- * Highly Stable Oxide Passivated Junction

SYMBOL




ORDERING INFORMATION

Ordering Number		Package	Pin Assignment			Packing
Lead Free	Halogen Free		1	2	3	
MBR10150L-TA3-T	MBR10150G-TA3-T	TO-220	A	K	A	Tube
MBR10150L-TF3-T	MBR10150G-TF3-T	TO-220F	A	K	A	Tube
MBR10150L-T27-T	MBR10150G-T27-T	TO-277	A	K	A	Tape Reel
MBR10150L-Z21D-B	MBR10150G-Z21D-B	DO-201AD	K	A	-	Tape Box

Note: Pin Assignment: A: Anode K: Cathode

	(1) Packing Type (2) Package Type (3) Green Package	(1) T: Tube, R: Tape Reel, B: Tape Box (2) TA3: TO-220, TF3: TO-220F, TND: TO-252D T27: TO-277, Z21D: DO-201AD (3) G: Halogen Free and Lead Free, L: Lead Free
--	--	--



MARKING

PACKAGE	MARKING
TO-220 / TO-220F TO-252D	UTC MBR10150 Lot Code → → → → → Date Code 1 L: Lead Free G: Halogen Free
TO-277	UTC MBR10150 Lot Code → → → → → Date Code L: Lead Free G: Halogen Free
DO-201AD	MBR10150 → Cathode Band for uni-directional Only → Date Code

■ ABSOLUTE MAXIMUM RATING ($T_A=25^{\circ}\text{C}$, unless otherwise specified)

Ratings at 25°C ambient temperature unless otherwise specified.

Single phase half-wave 60Hz, resistive or inductive load, for capacitive load current derate by 20%.

PARAMETER	SYMBOL	RATINGS	UNIT
Working Peak Reverse Voltage	V_{RWM}	150	V
Repetitive Peak Reverse Voltage	V_{RRM}	150	V
DC Blocking Voltage	V_R	150	V
Average Rectified Output Current ($T_A=105^{\circ}\text{C}$)	I_O	10	A
Peak Forward Surge Current 8.3ms Single Half Sine-Wave Superimposed on Rated Load	I_{FSM}	170	A
Junction Temperature	T_J	$-55 \sim +150$	$^{\circ}\text{C}$
Storage Temperature	T_{STG}	$-55 \sim +150$	$^{\circ}\text{C}$

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ THERMAL DATA

PARAMETER	SYMBOL	RATINGS	UNIT
Typical Thermal Resistance	TO-220	2	$^{\circ}\text{C/W}$
	TO-220F	4	$^{\circ}\text{C/W}$
	TO-252D	2.5	$^{\circ}\text{C/W}$
	DO-201AD	22	$^{\circ}\text{C/W}$
	TO-277	72 (Note)	$^{\circ}\text{C/W}$

Note: FR-4 PCB, 2 oz Copper. Minimum recommended pad layout.

■ ELECTRICAL CHARACTERISTICS

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Instantaneous Forward Voltage Drop	V_F	$I_F=10\text{A}$, $T_C=25^{\circ}\text{C}$			0.93	V
		$I_F=10\text{A}$, $T_C=125^{\circ}\text{C}$			0.83	
Instantaneous Reverse Current	I_R	Rated DC Voltage, $T_C=25^{\circ}\text{C}$			500	μA
		Rated DC Voltage, $T_C=125^{\circ}\text{C}$			20	mA

Note: Pulse Test: Pulse width $\leq 300\mu\text{s}$, Duty cycle $\leq 2\%$.

UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.