



MBR3150

Preliminary

DIODE

3.0A SCHOTTKY BARRIER RECTIFIER

■ DESCRIPTION


The UTC **MBR3150** is a 3.0A schottky barrier rectifier, it uses UTC's advanced technology to provide the customers with high surge capability, high efficiency, high current capability, low power loss and low forward voltage drop, etc.

The UTC **MBR3150** is suitable for free wheeling and polarity protection, etc.

■ FEATURES

- * Low forward voltage drop, High Current Capability
- * Low power loss, High efficiency
- * High Surge Capability
- *For Use in Low Voltage,High Frequency Inverters and Polarity Protection Applications.

■ SYMBOL



■ ORDERING INFORMATION


Ordering Number		Package	Pin Assignment		Packing
Lead Free	Halogen Free		1	2	
MBR3150L-Z21D-R	MBR3150G-Z21D-R	DO-201AD	K	A	Tape Box
MBR3150L-SMA-R	MBR3150G-SMA-R	SMA	K	A	Tape Reel

Note: Pin Assignment: A: Anode K: Cathode

<p>MBR3150G-Z21D-B</p> <ul style="list-style-type: none"> (1)Packing Type (2)Package Type (3)Green Package 	<ul style="list-style-type: none"> (1) B: Tape Box, R: Tape Reel (2) Z21D: DO-201AD, SMA: SMA (3) G: Halogen Free and Lead Free, L: Lead Free
---	--

■ MARKING

SMA	DO-201AD / DO-201AD1
<p>UTC □□□□ → Date Code R3150 □ → L: Lead Free G: Halogen Free</p> <p>← Cathode Band for uni-directional Only</p>	<p>→ Cathode Band for uni-directional Only</p> <p>MBR3150 □ → L: Lead Free G: Halogen Free □□□□ → Date Code</p>



■ ABSOLUTE MAXIMUM RATING ($T_A=25^{\circ}\text{C}$, unless otherwise specified)

Ratings at 25°C ambient temperature unless otherwise specified.

Single phase half-wave 60Hz, resistive or inductive load, for capacitive load current derate by 20%.

PARAMETER	SYMBOL	RATINGS	UNIT
Working Peak Reverse Voltage	V_{RWM}	150	V
Repetitive Peak Reverse Voltage	V_{RRM}	150	V
Maximum RMS Reverse Voltage	$V_{R(RMS)}$	105	V
DC Blocking Voltage	V_R	150	V
Average Rectified Output Current	I_O	3.0	A
Peak Forward Surge Current 8.3ms Single Half Sine-Wave Superimposed on Rated Load	I_{FSM}	80	A
Junction Temperature	T_J	-55 ~ +150	$^{\circ}\text{C}$
Storage Temperature	T_{STG}	-55 ~ +150	$^{\circ}\text{C}$

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged. Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ THERMAL DATA (Note)

PARAMETER	SYMBOL	RATINGS	UNIT
Typical Thermal Resistance	SMA	32	$^{\circ}\text{C}/\text{W}$
	DO-201AD	20	

Note: Mounted on an FR4 PCB, single-sided copper, with 100 cm^2 copper pad area.

■ ELECTRICAL CHARACTERISTICS

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Reverse Breakdown Voltage (Note 2)	$V_{(BR)R}$	$I_R=0.50\text{mA}$	150			V
Instantaneous Forward Voltage Drop (Note 1)	V_{FM}	$I_F=3\text{A}, T_C=25^{\circ}\text{C}$			0.9	V
		$I_F=3\text{A}, T_C=125^{\circ}\text{C}$			0.7	V
Peak Reverse Current at Rated DC Blocking Voltage (Note 2)	I_{RM}	Rated DC Voltage, $T_C=25^{\circ}\text{C}$			50	μA
		Rated DC Voltage, $T_C=100^{\circ}\text{C}$			10	mA

Note: Pulse Test: Pulse width $\leq 300\mu\text{s}$, Duty cycle $\leq 2\%$.

+

UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.