

**UTC** UNISONIC TECHNOLOGIES CO., LTD

### **ULC8740**

# LOW POWER, SINGLE-SUPPLY, **RAIL-TO-RAIL I/O** COMPARATOR

#### DESCRIPTION

The ULC8740 is a single high-speed comparator optimized for systems powered from a 3V or 5V supply. The device features high-speed response, low-power consumption, and rail-to-rail input range. Propagation delay is 45ns, while supply current is only 200µA.

The UTC ULC8740 supports rail-to-rail input and output operation. The input common mode voltage range is from -0.1V to  $(V^+)$  + 0.1V, and the output voltage swing is within 0.3V of the rails without external pull-up or pull-down resistor. The device can be compatible with CMOS and TTL logics. Any input or output pin has a continuous short-circuit protection to both power supply rails.

The UTC ULC8740 has an internal hysteresis for reducing comparator sensitivity to noise, even when the input signals move slowly.

#### **FEATURES**

- \* Supply Voltage Range: 2.7V to 5.5V
- \* Low Supply Current: 200µA (Typ.) at V<sup>+</sup> = 5V
- \* Low Offset Voltage: 1mV (Typ.)
- \* Rail-to-Rail Input and Output
- \* Supports CMOS or TTL Logic

\* Internal Hysteresis for Reducing Comparator Sensitivity to Noise

#### ORDERING INFORMATION

Ordering Number		Deskere	Deaking	
Lead Free	Halogen Free	Раскаде	Раскіпд	
ULC8740L-AF5-R	ULC8740G-AF5-R	SOT-25	Tape Reel	
ULC8740L-AL5-R	ULC8740G-AL5-R	SOT-353	Tape Reel	

ULC8740G-AF5-R T(1)Packing Type	(1) R: Tape Reel
(2)Package Type	(2) AF5: SOT-25, AL5: SOT-353
(3)Green Package	(3) G: Halogen Free and Lead Free, K: Lead Free



## ULC8740

### MARKING



#### PIN CONFIGURATION



#### PIN DESCRIPTION

PIN NO.	PIN NAME	DESCRIPTION
1	OUT	Output
2	V-	Negative power supply
3	+IN	Non-inverting Input
4	-IN	Inverting Input
5	V+	Positive power supply

#### BLOCK DIAGRAM





#### ■ ABSOLUTE MAXIMUM RATING (T<sub>A</sub>=25°C, unless otherwise specified)

PARAMETER	SYMBOL	RATINGS	UNIT
Supply Voltage	V+ - V-	6	V
Input Voltage	V <sub>IN</sub>	V⁻ - 0.3 ~ V⁺ + 0.3	V
Differential Input Voltage	V <sub>ID</sub>	V <sup>+</sup>	V
Output Voltage	Vo	V <sup>-</sup> - 0.3 ~ V <sup>+</sup> + 0.3	V
Junction Temperature	TJ	+150	°C
Storage Temperature Range	T <sub>STG</sub>	-65 ~ +150	°C

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged. Absolute maximum ratings are stress ratings only and functional device operation is not implied.

#### RECOMMENDED OPERATING CONDITIONS

Over operating free-air temperature range (unless otherwise specified)

PARAMETER	SYMBOL	MIN	TYP	MAX	UNIT
Supply Voltage	V+ - V-	2.7		5.5	V
Operating Free-Air Temperature	TOPR	-40		+85	°C

#### ELECTRICAL CHARACTERISTICS

(V\*=5.0V, V<sub>CM</sub>=0V, C<sub>L</sub>=15pF, typical values are at T<sub>A</sub>=25°C, unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Supply Current/Amplifier	lα	V <sup>+</sup> = 3V, I <sub>OUT</sub> = 0mA		190	240	μA
Supply Current/Amplifier		V <sup>+</sup> = 5V, I <sub>OUT</sub> = 0mA		200	250	μA
Power Supply Rejection Ratio	PSRR	V <sub>CM</sub> = 0V, V <sup>+</sup> = 2.7V to 5.5V	59	70		dB
Input Offset Voltage (Note 3)	Vos	V <sup>+</sup> = 5V, V <sub>CM</sub> = 0V		1	5	mV
Input Common Mode Voltage Range	Vсм		-0.1		V++ 0.1	V
Common Mode Rejection Ratio (Note4)	CMRR	V <sup>+</sup> = 5V, $V_{CM}$ = 0V to 5V	60	75		dB
Input Hysteresis (Note 5)	V <sub>HYST</sub>	$V^{+}=5V, V_{CM}=0V$		3.5		mV
Output Shart Circuit Current	ISOURCE	$V^+=5V$ , Out to $V_S/2$	21	28		mA
Output Short-Circuit Current	I <sub>SINK</sub>	$V^+=5V$ , Out to $V_S/2$		-28	-20	mA
Output \ /oltono Output from Doil	Vон	V⁺= 5V, I <sub>OUT</sub> = 4mA		240	450	mV
Output voltage Swing from Rail	V <sub>OL</sub>	V <sup>+</sup> = 5V, I <sub>OUT</sub> = -4mA		200	231	mV
Proposition Doloy (Low to Llink)	tplh	V <sup>+</sup> = 3V, Overdrive = 10mV		35		ns
Propagation Delay (Low to Hign)		V <sup>+</sup> = 3V, Overdrive = 100mV		30		ns
Dreperation Delay (Link to Law)	<b>t</b> PHL	V <sup>+</sup> = 3V, Overdrive = 10mV		45		ns
Propagation Delay (High to Low)		V <sup>+</sup> = 3V, Overdrive = 100mV		30		ns
Rise Time	trise	V <sup>+</sup> = 3V, Overdrive = 10mV		9		ns
		V <sup>+</sup> = 3V, Overdrive = 100mV		8		ns
	t <sub>FALL</sub>	V <sup>+</sup> = 3V, Overdrive = 10mV		8		ns
		V <sup>+</sup> = 3V. Overdrive = 100mV		5		ns

Notes: 1.  $V_{\text{OS}}$  is the midway voltage for the hysteresis zone of the comparator.

2. CMRR is defined over the condition of whole input common mode range.

3. The input hysteresis is the gap between the upper threshold where the output of the comparator switches to high position and the lower threshold where the output of the comparator switches to low position.



### TYPICAL APPLICATION CIRCUIT



Figure 1. A Threshold Detector Controlled by 8-Bit DAC



Figure 2. The Application of Line Receiver



## ULC8740



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

