

**UTG15N135LNS1**

Preliminary


*Insulated Gate Bipolar Transistor***1350V SMPS N-CHANNEL IGBT****DESCRIPTION**

The UTC **UTG15N135LNS1** is a N-channel IGBT. it uses UTC's advanced technology to provide customers with high input impedance, high switching speed and low conduction loss, etc.

The UTC **UTG15N135LNS1** is suitable for high voltage switching, high frequency switch mode power supplies.

FEATURES


- * High switching speed
- * High avalanche ruggedness
- * Low saturation voltage: $V_{CE(SAT), Typ.} = 1.97V @ I_C=15A, V_{GE}=15V$ ($T_C = 25^\circ C$)

SYMBOL**ORDERING INFORMATION**


Ordering Number		Package	Pin Assignment			Packing
Lead Free	Halogen Free		1	2	3	
UTG15N135LNS1L-T47-T	UTG15N135LNS1G-T47-T	TO-247	G	C	E	Tube
UTG15N135LNS1L-T3P-T	UTG15N135LNS1G-T3P-T	TO-3P	G	C	E	Tube
UTG15N135LNS1L-T3N-T	UTG15N135LNS1G-T3N-T	TO-3PN	G	C	E	Tube

Note: Pin Assignment: G: Gate C: Collector E: Emitter

UTG15N135LNS1G-T47-T		(1) Packing Type	(1) T: Tube
		(2) Package Type	(2) T47: TO-247, T3P: TO-3P, T3N: TO-3PN
		(3) Green Package	(3) G: Halogen Free and Lead Free, L: Lead Free



■ MARKING



■ ABSOLUTE MAXIMUM RATINGS (T_A=25°C, unless otherwise specified)

PARAMETER		SYMBOL	RATINGS	UNIT
Collector-Emitter Voltage		V _{CES}	1350	V
Gate-Emitter Voltage		V _{GES}	±20	V
Transient Gate-Emitter Voltage (t _p < 5 ms)			±25	V
Continuous Collector Current	T _C =25°C	I _C	30	A
	T _C =100°C		15	A
Collector Current Pulsed (Note 1)		I _{CM}	60	A
Diode Forward Current	T _C =25°C	I _F	30	A
	T _C =100°C		15	A
Power Dissipation (T _C =25°C)	TO-247	P _D	245	W
	TO-3P/TO-3PN		260	W
Operating Junction Temperature		T _J	-40 ~ +150	°C
Storage Temperature Range		T _{STG}	-55 ~ +150	°C

Notes: 1. Absolute maximum ratings are stress ratings only and functional device operation is not implied.

Absolute maximum ratings are those values beyond which the device could be permanently damaged.

2. Pulse width limited by maximum junction temperature.

■ THERMAL DATA

PARAMETER		SYMBOL	RATING	UNIT
Junction to Case	TO-247	θ_{JC}	0.51	°C/W
	TO-3P/TO-3PN		0.48	°C/W

■ ELECTRICAL CHARACTERISTICS (T_C=25°C, unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
OFF CHARACTERISTICS						
Collector-Emitter Breakdown Voltage	BV _{CES}		1350			V
Collector Cut-Off Current	I _{CES}	V _{CE} =1350V, V _{GE} =0V			5	μA
G-E Leakage Current	I _{GES}	V _{CE} =0V, V _{GE} =±20V			±250	nA
ON CHARACTERISTICS						
Gate to Emitter Threshold Voltage	V _{GE(TH)}	I _C =250μA, V _{CE} =V _{GE}	3.5		6.5	V
Collector to Emitter Saturation Voltage	V _{CE(SAT)}	I _C =15A, V _{GE} =15V	T _C =25°C	1.97	2.4	V
			T _C =125°C	2.7		V
DYNAMIC CHARACTERISTICS						
Input Capacitance	C _{IES}	V _{CE} =25V, V _{GE} =0V, f=1MHz		1960		pF
Output Capacitance	C _{OES}			46		pF
Reverse Transfer Capacitance	C _{RES}			24		pF
SWITCHING CHARACTERISTICS						
Total Gate Charge	Q _G	V _{CE} =600V, I _C =15A, V _{GE} =15V		98		nC
Gate-Emitter Charge	Q _{GE}			24		nC
Gate-Collector Charge	Q _{GC}			38		nC
Turn-On Delay Time	t _{DON}	V _{CC} =600V, I _C =15A, R _G =5Ω, V _{GE} =0~15V, L=500μH		12		ns
Rise Time	t _R			23		ns
Turn-Off Delay Time	t _{DOFF}			96		ns
Fall Time	t _F			210		ns
Turn-On Switching Loss	E _{ON}			1.05		mJ
Turn-Off Switching Loss	E _{OFF}			0.77		mJ
SOURCE- DRAIN DIODE RATINGS AND CHARACTERISTICS						
Forward Voltage Drop	V _F	I _F =15A			3.0	V
Reverse Recovery Time	t _{rr}	I _F =15A, dI/dt=100A/μS, V _{CC} =400V		56		ns
Reverse Recovery Charge	Q _{rr}			1577		μC

■ TEST CIRCUIT AND WAVEFORMS




Fig 1. INDUCTIVE SWITCHING TEST CIRCUIT




Fig 2. SWITCHING TEST WAVEFORMS

UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.