



FT5045-P150D

Preliminary


DIODE


SCHOTTKY BYPASS DIODE MODULE

■ FEATURES

- * Ultra low forward voltage, low power loss
- * Low leakage current
- * High surge current

■ SYMBOL


FT-A	FT-B
A  K	K  A




■ ORDERING INFORMATION

Ordering Number		Package	Packing
Lead Free	Halogen Free		
FT5045L-P150D-FTA-T	FT5045G-P150D-FTA-T	FT-A	Tube
FT5045L-P150D-FTB-T	FT5045G-P150D-FTB-T	FT-B	Tube

Note: Pin Assignment: A: Anode K: Cathode

FT5045G-P150D-FTA-T	
	(1) Packing Type (2) Package Type (3) Wafer Size Code (4) Green Package
	(1) T: Tube (2) FTA: FT-A, FTB: FT-B (3) P150D (4) G: Halogen Free and Lead Free, L: Lead Free

■ MARKING



■ ABSOLUTE MAXIMUM RATINGS ($T_A=25^{\circ}\text{C}$ unless otherwise specified)

Single phase, half wave, 60Hz, resistive or inductive load.

For capacitance load, derate current by 20%.

PARAMETER	SYMBOL	RATINGS	UNIT
DC Blocking Voltage	V_{RM}	45	V
Working Peak Reverse Voltage	V_{RWM}	45	V
Peak Repetitive Reverse Voltage	V_{RRM}	45	V
RMS Voltage	V_{RMS}	31.5	V
Average Rectified Output Current @ 60Hz Half Sine-Wave, R-Load	I_O	50	A
Peak Forward Surge Current 8.3ms Single Half Sine-Wave Superimposed on Rated Load Per Diode	I_{FSM}	700	A
Operating Junction Temperature (In DC Forward Mode Operation Without Reverse Bias) ($t \leq 1\text{h}$)	T_J	$-55 \sim +200$	$^{\circ}\text{C}$
Storage Temperature	T_{STG}	$-55 \sim +150$	$^{\circ}\text{C}$

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged.
Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ THERMAL CHARACTERISTICS (PER LEG)

PARAMETER	SYMBOL	RATINGS	UNIT
Typical Thermal Resistance	θ_{JC}	0.7	$^{\circ}\text{C/W}$

■ ELECTRICAL CHARACTERISTICS (PER LEG) ($T_A=25^{\circ}\text{C}$ unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Reverse Breakdown Voltage	$V_{(BR)R}$	$I_R=0.50\text{mA}$	45			V
Maximum Instantaneous Forward Voltage Drop per Diode	V_F	$I_F=50\text{A}$, $T_C=25^{\circ}\text{C}$			0.55	V
Reverse Leakage Current @ V_R	I_R	$V_R=40\text{V}$, $T_C=25^{\circ}\text{C}$			100	μA
		$V_R=40\text{V}$, $T_C=125^{\circ}\text{C}$			12	mA

Note: Pulse Test: Pulse width $\leq 300\mu\text{s}$, Duty cycle $\leq 2\%$.

UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.