



USC075R011A

Power MOSFET

45A, 750V N-CHANNEL SILICON CARBIDE PLANAR ENHANCEMENT POWER MOSFET

DESCRIPTION



SiC The material can achieve high voltage with most carrier devices (MOSFET) with fast device structure characteristics, so it can realize the three characteristics of "high voltage", "low on resistance" and "high frequency" at the same time.

It is widely used in electric vehicle charger, industrial equipment power supply, efficient power regulator inverter and rectification part and other uses.

FEATURES

- * $R_{DS(ON)} \leq 15 \text{ m}\Omega$ @ $V_{GS}=18\text{V}$, $I_D=80\text{A}$
- * High Blocking Voltage
- * High Frequency Operation
- * Low on-resistance
- * Fast intrinsic diode with low reverse recovery
- * 100% avalanche tested

SYMBOL



TO-247-4


ORDERING INFORMATION

Ordering Number		Package	Pin Assignment				Packing
Lead Free	Halogen Free		1	2	3	4	
USC075R011AL-T474-T	USC075R011AG-T474-T	TO-247-4	D	S	S	G	Tube

Note: Pin Assignment: D: Drain S: Source G: Gate

USC075R011AG-T474-T (1) Packing Type (2) Package Type (3) Green Package	(1) T: Tube (2) T474: TO-247-4 (3) G: Halogen Free and Lead Free, L: Lead Free
---	---

MARKING



ABSOLUTE MAXIMUM RATINGS (T_C=25°C, unless otherwise specified)

PARAMETER			SYMBOL	RATINGS	UNIT
Drain-Source Voltage			V _{DSS}	750	V
Gate-Source Voltage	Dynamic		V _{GSS}	-10 / +23	V
	Static			-4 / +18	V
Drain Current	Continuous	V _{GS} =18A T _C =25°C	I _D	145	A
		V _{GS} =18A T _C =100°C		103	A
	Pulsed (Note 2)		I _{DM}	450	A
Power Dissipation			P _D	484	W
Junction Temperature			T _J	-55 ~ +175	°C
Storage Temperature			T _{STG}	-55 ~ +175	°C

Notes: 1. Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

2. Repetitive Rating: Pulse width limited by maximum junction temperature.







■ THERMAL DATA

PARAMETER	SYMBOL	RATINGS	UNIT
Junction to Ambient	θ _{JA}	50	°C/W
Junction to Case	θ _{JC}	0.31	°C/W







■ ELECTRICAL CHARACTERISTICS (T_J=25°C, unless otherwise specified)

PARAMETER		SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
OFF CHARACTERISTICS							
Drain-Source Breakdown Voltage		BV _{DSS}	I _D =100μA, V _{GS} =0V	750			V
Zero Gate Voltage Drain Current		I _{DSS}	V _{DS} =750V, V _{GS} =0V	0	1	50	μA
Gate- Source Leakage Current	Forward	I _{GSS}	V _{GS} =+18V, V _{DS} =0V	0	1	200	nA
	Reverse		V _{GS} =-4.0V, V _{DS} =0V	-200	-1	0	nA
ON CHARACTERISTICS							
Gate Threshold Voltage	V _{GS(TH)}	V _{DS} =V _{GS} , I _D =27mA	2.0	2.7	3.7	V	
		V _{DS} =V _{GS} , I _D =27mA, T _J =150°C		2.1		V	
		V _{DS} =V _{GS} , I _D =27mA, T _J =175°C		2.0		V	
Static Drain-Source On-State Resistance	R _{DS(ON)}	V _{GS} =18V, I _D =80A		11.6	15	mΩ	
		V _{GS} =18V, I _D =80A, T _J =150°C		15		mΩ	
		V _{GS} =18V, I _D =80A, T _J =175°C		16		mΩ	
Transconductance	g _{FS}	V _{DS} =20V, I _D =80A		58		S	
		V _{DS} =20V, I _D =80A, T _J =150°C		52		S	
		V _{DS} =20V, I _D =80A, T _J =175°C		51		S	
DYNAMIC PARAMETERS							
Input Capacitance	C _{ISS}	V _{DS} =400V, V _{GS} =0V, f=1MHz		4465		pF	
Output Capacitance	C _{OSS}			335		pF	
Reverse Transfer Capacitance	C _{RSS}			28		pF	
C _{OSS} Stored Energy	E _{OSS}			36		μJ	
SWITCHING PARAMETERS							
Total Gate Charge	Q _G	V _{DS} =400V, V _{GS} =-4V / +18V, I _D =80A		217		nC	
Gate to Source Charge	Q _{GS}			56		nC	
Gate to Drain Charge	Q _{GD}			83		nC	
Internal Gate Input Resistance	R _{G(int)}	I _D =0A, f=1MHz		1.3		Ω	
Turn-ON Switching Energy	E _{ON}	V _{DS} =400V, V _{GS} =-4V / +18V, I _D =80A, R _{G(ext)} =2Ω, L=100μH		430		μJ	
Turn-OFF Switching Energy	E _{OFF}			70		μJ	
Turn-ON Delay Time	t _{D(ON)}			18		ns	
Rise Time	t _R			21		ns	
Turn-OFF Delay Time	t _{D(OFF)}			41		ns	
Fall-Time	t _F			8		ns	
SOURCE- DRAIN DIODE RATINGS AND CHARACTERISTICS							
Drain-Source Diode Forward Voltage	V _{SD}	V _{GS} =-4.0V, I _{SD} =40A		4.0		V	
		V _{GS} =-4.0V, I _{SD} =40A, T _J =150°C		3.6		V	
		V _{GS} =-4.0V, I _{SD} =40A, T _J =175°C		3.5		V	
Continuous Diode Forward Current	I _S	V _{GS} =-4.0V			100	A	
Body Diode Reverse Recovery Time	t _{rr}	V _{GS} =-4.0V, I _{SD} =80A, V _R =400V, diF/dt=4200A/μs		19		ns	
Body Diode Reverse Recovery Charge	Q _{rr}			390		nC	
Peak Reverse Recovery Current	I _{rrm}			36		A	




TYPICAL CHARACTERISTICS



TYPICAL CHARACTERISTICS (Cont.)



■ TYPICAL CHARACTERISTICS (Cont.)



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.