


**UCBD40120SA****SiC-SBD DIODE****SILICON CARBIDE
SCHOTTKY BARRIER DIODES****DESCRIPTION**


The **UCBD40120SA** is an SiC Schottky barrier diodes (SBDs) feature high reverse voltage ratings. In addition to SBDs with short reverse recovery time (t_{rr}), provides 1200V SBDs with a junction barrier Schottky (JBS) structure that provide low leakage current (I_r) and high surge current capability required for switched-mode power supplies. These devices help improve the efficiency of switched-mode power supplies.



TO-247-2

FEATURES


- * Zero Reverse Recovery Current
- * Humidity Resistant
- * High Frequency Operation
- * Temperature-Independent Switching Behavior

SYMBOL**ORDERING INFORMATION**

Ordering Number		Package	Pin Assignment		Packing
Lead Free	Halogen Free		1	2	
UCBD40120SAL-T472-T	UCBD40120SAG-T472-T	TO-247-2	K	A	Tube

Note: Pin Assignment: K: Cathode A: Anode

UCBD40120SAG-T472-T	(1)Packing Type	(1) T: Tube
	(2)Package Type	(2) T472: TO-247-2
	(3)Green Package	(3) G: Halogen Free and Lead Free, L: Lead Free

MARKING

■ ABSOLUTE MAXIMUM RATINGS (T_C=25°C, unless otherwise specified)

Ratings at 25°C ambient temperature unless otherwise specified. Resistive or inductive load, 60Hz.

PARAMETER		SYMBOL	RATINGS	UNIT
Repetitive Peak Reverse Voltage		V _{RRM}	1200	V
Surge Peak Reverse Voltage		V _{RSM}	1200	V
DC Blocking Voltage		V _R	1200	V
Continuous Forward Current	T _C =25°C	I _F	97	A
	T _C =135°C		50	A
	T _C =149°C		40	A
Repetitive Peak Forward Surge Current	T _J =25°C t _P =10ms, Half Sine Wave	I _{FRM}	344	A
Non-Repetitive Peak Forward Surge Current	T _J =25°C t _P =10ms, Half Sine Wave	I _{FSM}	381	A
	T _J =110°C t _P =10ms, Half Sine Wave		360	A
Power Dissipation	T _C =25°C	P _D	600	W
	T _C =110°C		260	W
	T _C =150°C		100	W
Operating Junction Temperature		T _J	-55 ~ +175	°C
Storage Temperature Range		T _{STG}	-55 ~ +175	°C

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged.
Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ THERMAL DATA







PARAMETER	SYMBOL	RATINGS	UNIT
Junction to Case	θ _{JC}	0.25	°C/W

■ ELECTRICAL CHARACTERISTICS


(Ratings at 25°C ambient temperature unless otherwise specified. Resistive or inductive load, 60Hz)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
DC Blocking Voltage	V _{DC}	T _C =25°C	1200			V
Forward Voltage	V _F	I _F =20A, T _J =25°C		1.2		V
		I _F =40A, T _J =25°C		1.41	1.7	V
		I _F =40A, T _J =175°C		1.96		V
Reverse Current	I _R	V _R =1200V, T _J =25°C		1	100	μA
		V _R =1200V, T _J =175°C		8		μA
Total Capacitive Charge	Q _C	V _R =800V		227		nC
Total Capacitance	C	V _R =1V, f=1MHz		2235		pF
		V _R =400V, f=1MHz		197		pF
		V _R =800V, f=1MHz		155		pF
Capacitance Stored Energy	E _C	V _R =800V		50		μJ

■ TYPICAL CHARACTERISTICS



■ TYPICAL CHARACTERISTICS (Cont.)



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.