
UTG50N120LND2

Preliminary ***Insulated Gate Bipolar Transistor***

1200V TRENCH GATE FIELD-STOP IGBT



TO-247

■ DESCRIPTION


The UTC **UTG50N120LND2** is an Trench Field-Stop Insulated Gate Bipolar Transistor. it uses UTC's advanced technology to provide customers with high switching speed, low saturation voltage and low switching loss, etc.

The UTC **UTG50N120LND2** is suitable for the resonant or soft switching applications.

■ FEATURES

* High switching speed
* High avalanche ruggedness
* Low saturation voltage: $V_{CE(SAT).Typ.}$=1.9V @ I_C=50A, V_{GE}=15V (T_C =25°C)

■ SYMBOL



■ ORDERING INFORMATION


Ordering Number		Package	Pin Assignment			Packing
Lead Free	Halogen Free		1	2	3	
UTG50N120LND2L-T47-T	UTG50N120LND2G-T47-T	TO-247	G	C	E	Tube

Note: Pin Assignment: G: Gate C: Collector E: Emitter

UTG50N120LND2G-T47-T (1)Packing Type	(1) T: Tube
(2)Package Type	(2) T47: TO-247
(3)Green Package	(3) G: Halogen Free and Lead Free, L: Lead Free

Copyright © 2026 Unisonic Technologies Co., Ltd

■ MARKING


UTC UTG
50N120LND2□
L: Lead Free
G: Halogen Free
Lot Code
Date Code
1

■ ABSOLUTE MAXIMUM RATINGS (T_A=25°C, unless otherwise noted)

PARAMETER		SYMBOL	RATINGS	UNIT
Collector-Emitter Voltage		V_{CES}	1200	V
Gate-Emitter Voltage		V_{GES}	±20	V
Transient Gate-emitter voltage (t_p < 5 ms)			±25	V
Continuous Collector Current	T_C=25°C	I_C	100	A
	T_C=100°C		50	A
Collector Current Pulsed (Note 1)		I_{CM}	200	A
Diode Forward Current	T_C=25°C	I_F	100	A
	T_C=100°C		50	A
Short Circuit Withstand Time V_{GE} = 15V, V_{CC} ≤ 200V Allowed number of short circuits < 1000 Time between short circuits: ≥1.0s T_{VJ}= 25°C		t_{SC}	8	μs
Power Dissipation (T_C=25°C)		P_D	280	W
Operating Junction Temperature		T_J	-40 ~ +150	°C
Storage Temperature Range		T_{STG}	-55 ~ +150	°C

Notes: 1. Absolute maximum ratings are stress ratings only and functional device operation is not implied. Absolute maximum ratings are those values beyond which the device could be permanently damaged.
2. Pulse width limited by maximum junction temperature.

■ THERMAL DATA

PARAMETER	SYMBOL	RATING	UNIT
Junction to Case	θ_{JC}	0.44	°C/W

■ ELECTRICAL CHARACTERISTICS (T_C=25°C, unless otherwise noted)

PARAMETER	SYMBOL	TEST CONDITIONS		MIN	TYP	MAX	UNIT
OFF CHARACTERISTICS							
Collector-Emitter Breakdown Voltage	BV_{CES}			1200			V
Collector Cut-Off Current	I_{CES}	V_{CE}=1200V, V_{GE}=0V				5	μA
G-E Leakage Current	I_{GES}	V_{CE}=0V, V_{GE}=±20V				±400	nA
ON CHARACTERISTICS							
Gate to Emitter Threshold Voltage	$V_{GE(TH)}$	I_C=250μA, V_{CE}=V_{GE}		4.5		7.5	V
Collector to Emitter Saturation Voltage	$V_{CE(SAT)}$	I_C=50A, V_{GE}=15V	T_C=25°C		1.9	2.4	V
			T_C=125°C		2.3		V
DYNAMIC CHARACTERISTICS							
Input Capacitance	C_{IES}	V_{CE}=25V, V_{GE}=0V, f=1MHz			2.4		nF
Output Capacitance	C_{OES}				210		pF
Reverse Transfer Capacitance	C_{RES}				125		pF
SWITCHING CHARACTERISTICS							
Total Gate Charge	Q_G	V_{CE}=600V, I_C=50A, V_{GE}=15V			175		nC
Gate-Emitter Charge	Q_{GE}				23		nC
Gate-Collector Charge	Q_{GC}				116		nC
Turn-On Delay Time	$t_{DON)}$	V_{CC}=600V, I_C=50A, R_G=5Ω, V_{GE}=0~15V, L=500μH			18		ns
Rise Time	t_R				42		ns
Turn-Off Delay Time	$t_{DOFF)}$				219		ns
Fall Time	t_F				207		ns
Turn-On Switching Loss	E_{ON}				4.4		mJ
Turn-Off Switching Loss	E_{OFF}				3.7		mJ
SOURCE- DRAIN DIODE RATINGS AND CHARACTERISTICS							
Forward Voltage Drop	V_F	I_F=50A				3.5	V
Reverse Recovery Time	t_{rr}	I_F=50A, dI/dt=100A/μS, V_{CC}=600V			62		ns
Reverse Recovery Charge	Q_{rr}				1577		nC

■ TEST CIRCUIT AND WAVEFORMS




Fig 1. INDUCTIVE SWITCHING TEST CIRCUIT




Fig 2. SWITCHING TEST WAVEFORMS

UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.