
25A TRIACS




■ DESCRIPTION

The UTC **BTA24** is a 25A triacs which can be operated in 4 quadrants, it uses UTC's advanced technology to provide customers with high commutation performances.

The UTC **BTA24** is suitable for AC switching application and phase control application such as fan speed and temperature modulation control, lighting control and static switching relay, either in through-hole or surface-mount packages.

■ SYMBOL



■ ORDERING INFORMATION

Ordering Number		Package	Pin Assignment			Packing
Lead Free	Halogen Free		1	2	3	
BTA24L-x-xx-TA0-T	BTA24G-x-xx-TA0-T	TO-220A	MT1	MT2	G	Tube
BTA24L-x-xx-TF1-T	BTA24G-x-xx-TF1-T	TO-220F1	MT1	MT2	G	Tube
BTA24L-x-xx-TF3-T	BTA24G-x-xx-TF3-T	TO-220F	MT1	MT2	G	Tube
BTA24L-x-xx-T3F-T	BTA24G-x-xx-T3F-T	TO-3PF	MT1	MT2	G	Tube
BTA24L-x-xx-T3I-T	BTA24G-x-xx-T3I-T	TO-3PI	MT1	MT2	G	Tube

Note: Pin Assignment: MT1: MT1 MT2: MT2 G: Gate

BTA24G-x-xx-TA0-T
(1)Packing Type
(2)Package Type
(3)Sensitivity and type
(4)Voltage
(5)Green Package

(1) T: Tube
(2) TA0: TO-220A, TF1: TO-220F1, TF3: TO-220F
T3F: TO-3PF, T3I: TO-3PI
(3) refer to SENSITIVITY AND TYPE
(4) 6: 600V, 8: 800V
(5) G: Halogen Free and Lead Free, L: Lead Free


■ SENSITIVITY AND TYPE

PART NUMBER	VOLTAGE		SENSITIVITY	TYPE
	600V	800V		
BW	◎	◎	50mA	SNUBBERLESS
CW	◎	◎	35mA	SNUBBERLESS
SW	◎	◎	10mA	LOGIC LEVEL
TW	◎	◎	5mA	LOGIC LEVEL

◎: Available

Copyright © 2026 Unisonic Technologies Co., Ltd

■ MARKING



■ ABSOLUTE MAXIMUM RATINGS

PARAMETER			SYMBOL	RATINGS	UNIT
RMS On-State Current (Full Sine Wave)		T_C=75°C	$I_{T(RMS)}$	25	A
Non Repetitive Surge Peak On-State Current (Full Cycle, T_J initial=25°C)	F=50 Hz	t=20ms	I_{TSM}	250	A
	F=60 Hz	t=16.7ms		260	A
I^2t Value for Fusing	t_P=10ms		I^2t	340	A^2s
Critical Rate of Rise of On-State Current I_G=2xI_{GT}, tr≤100ns	F=120 Hz	T_J=125°C	dI/dt	50	A/μs
Non Repetitive Surge Peak Off-State Voltage	t_P=10ms	T_J=25°C	V_{DSM}/V_{RSM}	V_{DRM}/V_{RRM}+100	V
Peak Gate Current	t_P=20μs	T_J=125°C	I_{GM}	4	A
Average Gate Power Dissipation		T_J=125°C	$P_{G(AV)}$	1	W
Operating Junction Temperature			T_J	-40 ~ +125	°C
Storage Junction Temperature			T_{STG}	-40 ~ +150	°C

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged. Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ THERMAL DATA

PARAMETER		SYMBOL	RATINGS	UNIT
Junction to Ambient	TO-220A/TO-220F TO-220F1	θ_{JA}	60	°C/W
	TO-3PF		50	°C/W
	TO-3PI		40	°C/W
Junction to Case (AC)	TO-220A	θ_{JC}	0.8	°C/W
	TO-220F/TO-220F1		1.7	°C/W
	TO-3PF		1.4	°C/W
	TO-3PI		0.7	°C/W

■ ELECTRICAL CHARACTERISTICS (T_J=25°C unless otherwise specified)

FOR STANDARD TYPE (4 QUADRANTS)

PARAMETER	SYMBOL	TEST CONDITIONS		B			UNIT
				MIN	TYP	MAX	
Gate Trigger Current (Note 1)	I_{GT}	V_D=12V, R_L=33Ω	I-II-III			50	mA
			IV			100	mA
Gate Trigger Voltage	V_{GT}		ALL			1.3	V
Gate Non-Trigger Voltage	V_{GD}	V_D=V_{DRM}, R_L=3.3kΩ, T_J=125°C	ALL	0.2			V
Holding Current Note 2)	I_H	I_T=500mA				80	mA
Latching Current	I_L	I_G=1.2 I_{GT}	I-III-IV			70	mA
			II			160	mA
Critical Rate of Rise of Off-State Voltage (Note 2)	dV/dt	V_D=67%V_{DRM}, Gate Open, T_J=125°C		500			V/μs
Critical Rate of Rise of Off-State Voltage at Commutation(Note 2)	(dV/dt)c	(dI/dt)c=13.3A/ms, T_J= 125°C		10			V/μs

■ STATIC CHARACTERISTICS

PARAMETER	SYMBOL	TEST CONDITIONS		MIN	TYP	MAX	UNIT
Peak On-State Voltage (Note 2)	V_{TM}	I_{TM}=35A, t_P=380μs	T_J=25°C			1.55	V
Threshold Voltage (Note 2)	V_{TO}		T_J=125°C			0.85	V
Dynamic Resistance (Note 2)	R_D		T_J=125°C			16	mΩ
Repetitive Peak Off-State Current	I_{DRM}	V_{DRM}=V_{RRM}	T_J=25°C			5	μA
	I_{RRM}		T_J=125°C			3	mA

Notes: 1. Minimum I_{GT} is guaranteed at 5% of I_{GT} max.
2. For both polarities of MT2 referenced to MT1.

UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.